

Eng	Eco	Eco Plus	S13	S14	S16	S20	S14F	Kappa	Kappa 3	FL1	FL2	Pivot
Minimum dimensions	920 x 2050	500 x 1940	500 x 1910	500 x 1910	500 x 1910	500 x 1940	500 x 1910	500 x 1940	500 x 1920	500 x 1910	500 x 1910	1200 x 1950
Maximum dimensions	1020 x 2200	1100 x 2250	1400 x 3000	1400 x 3000	1400 x 3000	1400 x 3000	1100 x 2400	1250 x 3000	1250 x 3000	1400 x 3000	1400 x 3000	1950 x 3000
Option for per measure dimensions	X	●	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Frame lengths rebate	20mm	20mm	12mm	12mm	12mm	12mm	12mm	0mm	0mm	0mm	0mm	0mm
Header frame rebate	53mm	53mm	12mm	12mm	12mm	12mm	12mm	0mm	0mm	0mm	0mm	0mm
Doorleaf thickness	72mm	72mm	77mm	77mm	77mm	77mm	77mm	74mm	74mm	87mm	104mm	95mm
Doorleaf steel sheet thickness	2*0,6	2*0,6	2*0,8	2*0,8	2*0,8	3*0,8	2*0,8	2*0,8	2*0,8	2*0,8	2*0,8	2*0,8
Frame stell sheet thickness	1,5mm	1,5mm	2mm	2mm	2mm	2mm	2mm	2mm	2mm	2mm	2mm	2mm
Steel frame galvanised coating	X	●	●	●	●	●	●	●	●	●	●	✓
Frame colour black	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Frame colour RAL	X	●	●	●	●	●	●	●	●	●	●	●
Extra armour 1.25mm steel sheet	X	X	X	●	●	●	X	X	X	X	X	X
Bulletproof armour STARK (HARDOX 4mm)	X	X	X	●	●	●	X	X	X	X	X	X
Double door	X	X	●	●	●	●	X	●	●	●	●	X
Minimum width of 2nd leaf (door core)	X	X	220mm	220mm	220mm	220mm	X	220mm	220mm	230mm	230mm	X
Minimum width of fixed panel	X	200mm	200mm	200mm	200mm	200mm	X	220mm	220mm	200mm	200mm	200mm
Fixed Glass Panel	X	●	●	●	●	●	X	●	X	●	●	●
Fixed Panel	X	●	●	●	●	●	X	X	●	●	●	●
Flush fixed panel on the outside	X	●	●	●	●	●	X	●	●	X	●	●
Coplanar fixed panel on both sides	X	X	X	X	X	X	X	X	●	X	X	●
Lockcase SECUREMME 3-turn	✓	●	✓	●	●	●	✓	●	●	X	X	X
Lockcase ISEO Geared	X	✓	●	✓	✓	✓	●	✓	✓	✓	✓	✓
Lockcase MOTTURA 3D Key	X	●	●	●	●	●	●	●	●	●	●	●
Electric lockcase CISA	X	●	●	●	●	●	X	●	●	X	X	X
Electric lockcase ISEO LIGHT	X	X	X	X	X	X	X	X	X	●	●	●

Eng	Eco	Eco Plus	S13	S14	S16	S20	S14F	Kappa	Kappa 3	FL1	FL2	Pivot
Smart lockcase ISEO X1R Easy/Smart	X	X	●	●	●	X	X	●	●	●	●	●
Electric Striker with SEC 3- turn lockcase	●	●	●	●	●	●	●	●	●	X	X	X
Electric Striker with ISEO Geared lockcase	X	●	●	●	●	●	X	●	●	●	●	●
Panic bar lockcase	X	●	●	●	●	●	●	●	●	X	X	X
Cylinder SECUREMME K22	✓	X	X	X	X	X	✓	X	X	X	X	X
Cylinder ISEO R6 PLUS	●	✓	✓	✓	✓	✓	●	✓	✓	✓	✓	✓
Double function Cylinder ASTRA PRO 1	●	●	●	●	●	●	●	●	●	●	●	●
Cylinder MOTTURA CHAMPIONS PRO	●	●	●	●	●	●	●	●	●	X	X	X
Number of locking points	12	18	13	14	16	20	14	13	7	14	14	8
Number of moving locking points	7	13	7	8	10	14	8	7	7	8	8	8
Type of locking points	Single	Quad	Single	Single	Double	Quad	Single	Single	Single	Single	Single	Double
Hook locking points	X	X	●	●	●	●	X	●	●	●	●	X
Opening limiter	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	X
Extra locking	X	●	●	●	●	●	●	●	●	●	●	X
Number of hinges	2	2	2	2	2	3	2	2	2	2	2	n/a
Height adjustment	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Side adjustment	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
In-Out adjustment	X	X	X	X	X	X	X	✓	✓	X	X	X
External door closer	●	●	●	●	●	●	●	●	●	●	●	X
Concealed door closer	X	X	●	●	●	●	●	●	●	●	●	●
Peephole	✓	✓	✓	✓	✓	✓	X	✓	✓	●	●	●
Camera peephole	●	●	●	●	●	●	X	●	●	X	X	X
Rockwool insulation	X	●	●	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dropdown seal	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Steel threshold	X	X	●	●	●	●	✓	●	●	X	X	X

Eng	Eco	Eco Plus	S13	S14	S16	S20	S14F	Kappa	Kappa 3	FL1	FL2	Pivot
Aluminium threshold C 64x15	●	●	●	●	●	●	●*	●	●	✗	✗	✗
Water dripper C	●	●	●	●	●	●	●	●	●	✗	✗	✗
Alumunium Threshold PIVOT 71x9	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	●
Κατωκάσι & Νεροσταλλάκτης U	✗	✗	✗	●	●	●	✗	✗	●	✗	✗	✗
POLIS handle, shallow	●	●	●	●	●	●	●	●	●	●	●	●
POLIS handle	✗	✗	●	●	●	●	✗	●	●	●	●	●
ICON handle	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	●
SECRET handle	✗	✗	●	●	●	●	✗	●	●	●	●	●
Flush lever-turnkob ELXIS	✗	●	●	●	●	●	●	●	●	●	●	●
Flush lever-turnkob ELXIS in conjunction with concealed handle	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Aluminium handle	✓	✓	✓	●	●	●	✓	●	●	●	●	●
Praga or 1495 handle	●	●	●	✓	✓	✓	●	✓	✓	✓	✓	●
2145 handle	●	●	●	●	●	●	●	●	●	●	●	✓
Frame Eco	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Frame S	✗	✗	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗
Frame S FRANCE	✗	✗	●	●	●	●	●	✗	✗	✗	✗	✗
Frame S TETRAGON	✗	✗	●	●	●	●	●	✗	✗	●	✓	✗
Frame TETRAGON FRANCE	✗	✗	●	●	●	●	●	✗	✗	✓	●	✗
Frame RENO	✗	✗	●	●	●	●	✗	✗	✗	✗	✗	✗
Frame KAPPA	✗	✗	✗	✗	✗	✗	✗	✓	✓	✗	✗	✗
Frame PIVOT	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗	✓
Decorative frame E97X	●	●	●	●	●	●	●	✗	✗	✗	●	✗
Decorative frame E127X	●	●	●	●	●	●	●	●	●	✗	●	✗
External architraves 62x75	●	●	●	●	●	●	●	✗	✗	✗	●	✗
External architraves 62x95	✗	✗	✗	✗	✗	✗	✗	●	●	✗	✗	✗

Eng	Eco	Eco Plus	S13	S14	S16	S20	S14F	Kappa	Kappa 3	FL1	FL2	Pivot
External architraves E97	●	●	●	●	●	●	●	X	X	X	●	X
External architraves E127	●	●	●	●	●	●	●	●	●	X	●	X
External architraves ME77	X	X	X	X	X	X	X	X	X	X	X	●
External-Internal architraves ME120	X	X	X	X	X	X	X	X	X	X	X	●
Internal architraves M60	●	●	●	●	●	●	●	●	X	●	●	X
Internal architraves M90	X	X	X	X	X	X	X	●	X	X	X	X
Internal architraves M97	●	●	●	●	●	●	●	●	X	●	●	X
Internal architraves ME97	X	X	X	X	X	X	X	X	●	X	X	●
Internal architraves ME9.7.5	X	X	X	X	X	X	X	X	X	X	X	●
Steel restraint profile	✓	✓	X	X	X	X	✓	X	X	✓	✓	X
Pihaki M35 & second gasket	●	●	✓	✓	✓	✓	●	X	X	X	X	X
Aluminium restraint profile & second gasket	X	X	●	●	●	●	●	✓	✓	X	X	✓
Flush pihaki with panel (interior side)	●	●	●	●	●	●	●	X	X	X	X	X
Glass door SABA	X	X	●	●	●	●	X	●	●	●	X	X
Glass door SABA XL	X	X	●	●	●	●	X	●	●	●	X	X
Glass door SB5-DS	X	X	●	●	●	●	X	●	●	X	X	X
Glass door SB5-DTH	X	X	●	●	●	●	X	●	●	X	X	X
Glass door SB5	X	X	●	●	●	●	X	●	●	X	X	X
Glass door SABA KH	X	X	●	●	●	●	X	●	●	X	X	X
Anti-burglar resistance certification	n/a	-	-	RC3	RC3	RC3	RC3	-	-	-	-	-
Thermal conductivity certification	-	-	-	U=1,3	U=1,3	U=1,3	-	-	-	-	-	-
Sound insulation certification	-	-	-	37db	37db	37db	-	-	-	-	-	-
Fireproof certification	-	-	-	-	-	-	EI 45	-	-	-	-	-

The factory retains the right to change the equipment of each door with no warning. An always updated document of the door equipment is publicly available on the official website of the company
www.sabadoor.com

Standard Equipment ✓

Optional Equipment ●

Incompatible Equipment X